

ASME B30.14-2004
(Revision of ASME B30.14-1996)

Side Boom Tractors

**Safety Standard for Cableways, Cranes, Derricks, Hoists, Hooks, Jacks, and
Slings**

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**



The American Society of
Mechanical Engineers

A N A M E R I C A N N A T I O N A L S T A N D A R D

SIDE BOOM TRACTORS

ASME B30.14-2004

(Revision of ASME B30.14-1996)

SAFETY STANDARD FOR CABLEWAYS, CRANES, DERRICKS, HOISTS, HOOKS, JACKS, AND SLINGS

Date of Issuance: September 20, 2004

The next edition of this Standard is scheduled for publication in 2009. There will be no addenda issued to this edition.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Interpretations are published on the ASME Web site under the Committee Pages at <http://www.asme.org/codes/> as they are issued, and will also be published within the next edition of the Standard.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Three Park Avenue, New York, NY 10016-5990

Copyright © 2004 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword	iv
Committee Roster	v
B30 Series Introduction	vii
Summary of Changes	x
Chapter 14-0 Scope, Definitions, and References	1
Section 14-0.1 Scope of B30.14	1
Section 14-0.2 Definitions	1
Section 14-0.3 References	2
Chapter 14-1 Construction and Characteristics	4
Section 14-1.1 Load Ratings	4
Section 14-1.2 Boom Hoist and Load Hoist Mechanisms	4
Section 14-1.3 Side Boom Tractor Travel	6
Section 14-1.4 Controls	6
Section 14-1.5 Ropes and Reeving Accessories	6
Section 14-1.6 Cabs	7
Section 14-1.7 General Requirements	7
Chapter 14-2 Inspection, Testing, and Maintenance	9
Section 14-2.1 Inspection	9
Section 14-2.2 Testing	10
Section 14-2.3 Maintenance	10
Section 14-2.4 Rope Inspection, Replacement, and Maintenance	11
Chapter 14-3 Operation	13
Section 14-3.1 Operator Qualifications and Operating Practices	13
Section 14-3.2 Handling the Load	14
Section 14-3.3 Signals	14
Section 14-3.4 Miscellaneous	15
Figures	
1 Track-Type Tractor Side Boom	2
2 Wheel-Type Tractor Side Boom	2
3 Load Rating Chart	5
4 Standard Hand Signals for Controlling Side Boom Tractor Operations	16
5 Danger Zone for Side Boom Tractors and Lifted Loads Operating Near Electrical Transmission Lines	18
Table	
1 Required Clearance for Normal Voltage in Operation Near High Voltage Power Lines and Operation in Transit With No Load and Boom or Mast Lowered	18